ThinkVision T24d-10 61B4MAT1EU

Product

ThinkVision T24d-10

Machine Type

61B4

Region

EMEA

Display Size

24"

View Area

518.4x324 mm

Panel

In-Plane Switching

Aspect Ratio

16:10

Resolution

1920x1200

Pixel Pitch

0.27x0.27 mm

Dot / Pixel Per Inch

94 dpi

View Angle (H / V)

178 / 178

Response Time

7 ms

Color Support

16.7 Million

Refresh Rate

60 Hz

Brightness

300 nits

Contrast Ratio

1000:1

Color Gamut

99% sRGB

Curvature

None

Anti-glare

Yes

Video Connector

HDMI, DP, VGA

USB Port

5x USB 3.0

Camera

None

Microphone

None

Speakers

None

Power Consumption (Typical / Maximum)

22W / 64W

Power Adapter

Integrated

Stand

Tilt, Swivel, Pivot, Height Adjust Stand

Color

Black

Side Bezel Width

2 mm

Dimensions with Stand (HxWxD)

497.4x533.2x260.4 mm / 19.58x20.99x10.25 inches

Weight (Including Stand)

5.63 kg / 12.41 lbs.

Cables Included

DP cable, VGA cable

Environmental Certification

Energy Star Certified, TCO 7.0, TCO Edge 2.0, EPEAT Silver, ULE Gold. RoHS

Ergonomic Certification

TÜV Rheinland Eye Comfort

Base Warranty

3-year

Operating System Support

Support Windows 7, Windows 10

Sync Technology

None

Tiny Support / CPU / Platform

None / None / None

Ethernet / Bluetooth / Wireless

None / None / None

Touch Screen / Digitizer Pen / Battery

None / None / None

Display Ram / Storage / Card Slot

None / None / None

EAN/UPC/JAN

0191376269167 / 191376269167 / None

Announce Date

2017-06-13

WWW.LENOVO.COM

Lenovo may not offer the products, services or features discussed in this document in other countries. Lenovo may withdraw an offering at any time. Information is subject to change without notice. Consult your local representative for information on offerings available in your area.

Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. Lenovo provides this publication "as is" without warranty of any kind, either express or implied, including the implied warranties of merchantability or fitness for a



particular purpose.

https://psref.lenovo.com

Visit psref website for the latest version of Product specifications Reference.
© Lenovo, 2022. All rights reserved.



ThinkVision T24d-10 MONITOR

SPECIFICATIONS

DISPLAY		DIMENSIONS (W x D x H)	
Panel Size Panel Type Resolution Backlight Aspect Ratio Pixel Pitch (W x H) (mm) Dot/Pixel Per Inch (DPI/PPI) Anti-Glare Screen Dimensions (W x H) (mm) (inches) Maximum Brightness (Typical) Viewing Angle (H/V at CR 10:1) Contrast Ratio (Typical) Dynamic Contrast Ratio Color Gamut (CIE 1931) Display Colors (Typical) Response Time Extreme Typical Off	24" In-Plane Switching 1920 x 1200 WLED 16:10 0.27 x 0.27 94 PPI Yes 518.4 x 324 20.41" x 12.75" 300 cd/m² 178°/178° 1000:1 3M:1 99% sRGB 16.7 Million 4 ms 7 ms 15 ms	Size Packed (mm) (inches) Size Unpacked with Stand (mm) (inches) Size Monitor Head Only (mm) (inches) Distance from Table to Panel Lowest Pixel at Bottom of Screen (mm / inches) Highest Pixel at Top of Screen (mm / inches) Stand Base Footprint Area (mm) (inches) Weight Packed Unpacked Monitor Head Only	160 x 655 x 422 6.3" x 25.79" x 16.61" 533.2 x 260.4 x 497.4 20.99" x 10.25" x 19.58" 533.2 x 42.3 x 355.1 20.99" x 1.67" x 13.98" 56 / 2.2" 490 / 19.29" 250 x 250 9.84" x 9.84" Starting at 19.18 lbs (8.7 kg) Starting at 12.41 lbs (5.63 kg) Starting at 8.77 lbs (3.98 kg)
SIGNAL INPUT		POWER CONSUMPTION	

SIGNAL INPUT

Video Input Signals Video Cables Supplied	VGA + DisplayPort 1.2 + HDMI 1.4 VGA + DisplayPort + HDMI ¹
Video Cable Length	1.8 m
USB Hub	USB 3.0 ²
USB Cable Supplied	Yes
Audio-Out	Yes (3.5 mm)

Voltage Dynamic Frequency SIGNAL INTERFACE / PERFORMANCE **ENVIRONMENTAL**

Typical Maximum

Sleep-Mode

Power Supply

Power Voltage

Temperature Operating

Switch Off-Mode

Horizontal Frequency	30 kHz - 83 KHz
Vertical Frequency	50 Hz - 75 Hz
Native Resolution	1920 x 1200
Maximum Pixel Clock Speed/ Bandwidth	
VGA	205 MHz
HDMI™	165 MHz
DisplayPort™	165 MHz
Default Color Temperature	6500 K
Preset Display Modes	20
OSD Buttons	5
OSD Languages	English, French, German, Spanish, Italian, Japanese, Simplified Chinese, Russian

Non-Operating	-20°C – 60°C
Humidity	
Operating	10% - 80%
Non-Operating	5% - 95%
Altitude	
Operating	0 m – 5000 m
Non-Operating	0 ft - 40,000 ft
Arsenic-Free Glass	Yes
PVC-Free	Yes
Mercury-Free	Yes
PCC % of Plastic Resins	>85%

WARRANTY AND AVAILABILITY

MECHANICAL

Tilt Angle (Front / Back)

Till Aligie (Front / Dack)	3 / 30
Swivel Angle (Left / Right)	+/-45°
Lift (mm)	110
Pivot	+/-90°
VESA® Mount (mm x mm)	100 x 100
Cable Management	Yes
Kensington® Lock	Yes
Bezel Color	Business Black
Bezel Width	
Top (mm / inches)	2 / 0.08"
Bottom (mm / inches)	22.7 / 0.89"
Sides (mm / inches)	2 / 0.08"

-5°/30°

COMPLIANCE

Warranty

Geography Availability

EPEAT ENERGY STAR Rating ULE TCO ROHS (EU 2002/95/EC) China Energy Efficiency Standard Windows Cartification	Silver 8.0 Gold TCO Display 7.0 / TCO Edge 2.0 Yes Tier 2 Windows 7 / Windows 10
Windows Certification	Windows 7 / Windows 10

22 W

64 W

<0.3 W

<0.3 W

Internal

100 VAC - 240 VAC

50 Hz - 60 Hz

0°C - 40°C

3 Years

WW

US & Canada only.

² Depending on many factors such as the processing capability of peripheral devices, file attributes, and other factors related to system configuration and operating environments, the actual transfer rate using the various USB connectors on this device will vary and is typically slower than the data rates as defined by the respective USB specifications: - 5 Gbit/s for USB 3.1 Gen 1; 10 Gbit/s for USB 3.1 Gen 2 & 20 Gbit/s for USB 3.2.





WWW.LENOVO.COM











